

# Submersible Dewatering Pumps

## Munro FS Series 1/3 hp - 30 hp

### Pick-A-Pump

SUBMERSIBLE

TOTAL HEAD IN FEET	CHOOSING A MUNRO FS PUMP: FS250/400/750						HP RANGE: 1/3 - 1	PSI
	40	FS750	FS750					
30	FS400	FS750	FS750	FS750	FS750		12.93	
20	FS250	FS400	FS400	FS750	FS750	FS750	8.62	
10		FS250	FS250	FS400	FS400	FS750	4.31	
	20	30	40	50	60	70		

GALLONS PER MINUTE

TOTAL HEAD IN FEET	CHOOSING A MUNRO FS PUMP: FS215/315/222/322						HP RANGE: 2 - 3	PSI
	80	FS222	FS222					
70	FS222	FS222		FS237			30.17	
60	FS215	FS322	FS222/FS322	FS237			25.86	
50	FS315	FS215	FS322	FS222/FS322	FS237		21.55	
40	FS315	FS315	FS215/FS315	FS322	FS322		17.24	
30		FS315	FS215/FS315	FS215/315	FS322	FS322	12.93	
20					FS315	FS322	8.62	
	25	50	75	100	125	150		

GALLONS PER MINUTE

TOTAL HEAD IN FEET	CHOOSING A MUNRO FS PUMP: FS237/337/437/355/455						HP RANGE: 5 - 7 1/2	PSI
	90	FS237	FS355					
80	FS237/FS337	FS337	FS355				34.48	
70	FS455	FS237	FS355	FS355			30.17	
60	FS455	FS455	FS455	FS355			25.86	
50	FS437	FS437	FS337	FS455	FS455		21.55	
40		FS437	FS437	FS437	FS455	FS455	17.24	
30				FS437	FS437	FS455	12.93	
20						FS437	8.62	
10							4.31	
	50	100	150	200	250	300	350	

GALLONS PER MINUTE

TOTAL HEAD IN FEET	CHOOSING A MUNRO FS PUMP: FS411/475/611/675						HP RANGE: 10 - 15	PSI
	150	FS411						
140	FS411						60.34	
130	FS411	FS411					56.03	
120	FS475	FS411					51.72	
110	FS475	FS411	FS411				47.41	
100	FS611	FS475	FS411				43.10	
90	FS675	FS611	FS411				38.79	
80	FS675	FS675	FS611				34.48	
70		FS675	FS675	FS611			30.17	
60			FS475/FS675	FS611			25.86	
50				FS675	FS611		21.55	
40				FS675	FS611		17.24	
	100	200	300	400	500			

GALLONS PER MINUTE

TOTAL HEAD IN FEET	CHOOSING A MUNRO FS PUMP: FS6150/6220/8220						HP RANGE: 20 - 30	PSI	
	150	FS6220							64.65
140	FS6150	FS6220					60.34		
130	FS6150	FS6150	FS6220				56.03		
120	FS6150	FS6150	FS6220	FS6220			51.72		
110	FS6150	FS6150	FS6150	FS6220			47.41		
100	FS8220	FS8220	FS6150	FS6220			43.10		
90				FS8220	FS6220		38.79		
80				FS6150	FS8220		34.48		
70				FS6150	FS8220	FS8220	30.17		
60				FS6150	FS8220	FS8220	25.86		
50				FS6150	FS6220	FS8220	21.55		
	200	300	400	500	600	700	800	900	1000

GALLONS PER MINUTE

## Munro FS Series 1/3 hp - 30 hp

### Specifications – Pump

HP	Solids Handling in	Discharge Size in	Weight lbs	Model Number
1/3	.24	1.5	32	FS250S11
1/3	.24	1.5	32	FS250S22
1/2	.24	2	33	FS400S11
1/2	.24	2	33	FS400S22
1	.32	2	40	FS750S11
1	.32	2	37	FS750S22
1	.32	2	35	FS750T22
1	.32	2	35	FS750T44
2	.36	2	83	FS215S11
2	.36	2	81	FS215S22
2	.36	2	70	FS215T22
2	.36	2	60	FS215T44
2	.36	3	83	FS315S11
2	.36	3	81	FS315S22
2	.36	3	59	FS315T22
2	.36	3	78	FS315T44
3	.36	2	88	FS222T22
3	.36	2	68	FS222T44
3	.36	3	68	FS322T22
3	.36	3	69	FS322T44
5	.4	2	142	FS237T22
5	.4	2	122	FS237T44
5	.4	3	143	FS337T22
5	.4	3	135	FS337T44
5	.4	4	145	FS437T22
5	.4	4	144	FS437T44
7.5	.4	3	158	FS355T22
7.5	.4	3	148	FS355T44
7.5	.4	4	133	FS455T22
7.5	.4	4	148	FS455T44
10	.6	4	300	FS475T22
10	.6	4	300	FS475T44
10	.6	6	300	FS675T22
10	.6	6	300	FS675T44
15	.6	4	305	FS411T22
15	.6	4	307	FS411T44
15	.6	6	310	FS611T22
15	.6	6	311	FS611T44
20	.6	6	313	FS6150T22
20	.6	6	313	FS6150T44
30	.8	6	570	FS6220T22
30	.8	6	570	FS6220T44
30	.8	8	581	FS8220T22
30	.8	8	581	FS8220T44

SUBMERSIBLE